6" Snap-Pak Chimney

Material # Model #

Agency Listing: Built to UL103HT (2100° Intermittent, 1000° Continuous)

6" Wood-Burning	Chimney Len	gths and Fittin	gs (6" Inner Di	am 9" Outer Diam.)

Description

		3
F396	6 6SPS6-2	6" SS Chimney Length (2pk)
F396	7 6SPS12-2	12" SS Chimney Length (2pk)
F396	8 6SPS18-2	18" SS Chimney Length (2pk)
F396	9 6SPS24	24" SS Chimney Length
F397	0 6SPS36	36" SS Chimney Length
F397	1 6SPS48	48" SS Chimney Length
F397	2 6SPSE15-2	15° SS Elbow (2pk)
F397	3 6SPE30-2	30° SS Elbow (2pk)
F397	4 6SPFS	Firestop Spacer
F397	5 6SPIS	Insulation Shield
F397	6 6SPFF	Flat Flashing
F397	7 6SPF5	2/12-5/12 Flashing
F397	8 6SPF10	6/12-10/12 Flashing
F398	0 6SPRB	Roof Brace
F398	1 6SPSC	Storm Collar
F398	2 6SPC	Round Cap with Spark Arrester
F398	3 6SPWF	Non-Insulated Wall Firestop
F398	4 6SPAS	Adjustable Support
F398	5 6SPWB	Wall Band
F398	6 6SPSB	Support Band

6" Wood-Burning Chimney Components for Freestanding Stoves

F3987	6SPBSCS	Black Standard Ceiling Support
F3988	6SPBCCS	Black Cathedral Ceiling Support
F3989	6SPBTC	Black Trim Collar
F3990	6SPBSWA	Black Single Wall Pipe Adapter
F3991	6SPST	Tee SS (Tee Cap Included)
F3992	6SPTS	Tee Support
F3993	6SPATS	Adjustable Tee Support